



# The ES-30/30

Add Coin  
RMC to the ES-30/30  
for additional  
energy savings!



Full Speed and Efficiency, No Compromises

## FEATURES:

- 30-lb. x2 capacity
- Up to 25% more energy-efficient than any other dryer on the market \*
- Unsurpassed drying performance
- Single-phase reversing standard
- Four-point roller support system
- Dual-paned door glass
- Completely sealed basket
- 100% axial airflow
- Non-perforated ribs and basket
- Industry's only coin residual moisture control
- Available with optional stainless steel drum
- Available with optional stainless steel cabinet
- Backwardly inclined blower
- Self-diagnostic microprocessor controls

## ELECTRICAL SPECS:

Gas Models

SERVICE VOLTAGE	PHASE	WIRE SERVICE	APPROX. AMP DRAW		CIRCUIT BREAKER
			60 Hz	50 Hz	
120	1 $\emptyset$	2	8.9	--	15

\* Energy efficiency depends on load and installation.



Innovating Revolutions in Laundry

(508) 678-9000 • (508) 678-9447 fax • sales@amdry.com • www.amdry.com

# ES-30/30

MAXIMUM CAPACITY (DRY WEIGHT) PER POCKET		30 lb	13.61 kg
TUMBLER DIAMETER		25-3/4"	65.41 cm
TUMBLER DEPTH		34"	86.36 cm
TUMBLER VOLUME PER POCKET		10-1/4 cu ft	290.25 L
TUMBLER/DRIVE MOTOR PER POCKET		1/4 hp	0.19 kW
BLOWER/FAN MOTOR PER POCKET		1/2 hp	0.37 kW
DOOR OPENING (DIAMETER)		19-3/8"	49.21 cm
DOOR SILL HEIGHT TOP POCKET / BOTTOM POCKET		49" / 13"	124.46 cm / 33.02 cm
WATER CONNECTION		3/4"-11.5 NH (North America)	
		3/4" B.S.P.T. (Outside North America)	
DRYERS PER 20'/40' CONTAINER		14 / 28	
DRYERS PER 48'/53' TRUCK		36 / 38	
<b>Gas</b>	VOLTAGE AVAILABLE	120V	1ø 2w 60 Hz
	APPROXIMATE NET WEIGHT	535 lb	242.67 kg
	APPROXIMATE SHIPPING WEIGHT	560 lb	254.01 kg
	AIRFLOW PER POCKET	310 cfm	8.78 cmm
	HEAT INPUT PER POCKET	52,500 Btu/hr	13,230 kcal/hr
	EXHAUST CONNECTION (DIAMETER) PER POCKET	6"	15.24 cm
	COMPRESSED AIR CONNECTION	N / A	
	COMPRESSED AIR VOLUME	N / A	
	INLET PIPE CONNECTION PER POCKET	3/8" M.N.P.T.	
		3/8" M.B.S.P.T. (CE and Australia Only)	
<b>Electric</b>	VOLTAGE AVAILABLE	N / A	
	APPROXIMATE NET WEIGHT	N / A	
	APPROXIMATE SHIPPING WEIGHT	N / A	
	AIRFLOW PER POCKET	N / A	
	EXHAUST CONNECTION (DIAMETER) PER POCKET	N / A	
	COMPRESSED AIR CONNECTION	N / A	
	COMPRESSED AIR VOLUME	N / A	
OVEN SIZE PER POCKET			
	kW	Btu/hr	kcal/hr
<b>Steam</b>	VOLTAGE AVAILABLE	N / A	
	APPROXIMATE NET WEIGHT	N / A	
	APPROXIMATE SHIPPING WEIGHT	N / A	
	AIRFLOW PER POCKET	N / A	
	STEAM CONSUMPTION PER POCKET	N / A	
	OPERATING STEAM PRESSURE	N / A	
	EXHAUST CONNECTION (DIAMETER) PER POCKET	N / A	
	COMPRESSED AIR CONNECTION	N / A	
	COMPRESSED AIR VOLUME	N / A	
	BOILER HORSEPOWER (NORMAL LOAD) PER POCKET	N / A	
	SUPPLY CONNECTION PER POCKET	N / A	
RETURN CONNECTION PER POCKET	N / A		

Shaded areas are stated in metric equivalents

GS 2/12/09

