



# The ES-35/35

**Add Coin  
RMC to the ES-35/35  
for additional  
energy savings!**



**Full Speed and Efficiency, No Compromises**

## FEATURES:

- 35-lb. x2 capacity
- Up to 25% more energy-efficient than any other dryer on the market \*
- World's only 35 lb. stack
- Unsurpassed drying performance
- Single-phase reversing standard
- Four-point roller support system
- Dual-paned door glass
- Completely sealed basket
- 100% axial airflow
- Non-perforated ribs and basket
- Industry's only coin residual moisture control
- Available with optional stainless steel cabinet
- Available with optional stainless steel drum
- Backwardly inclined blower
- Self-diagnostic microprocessor control

## ELECTRICAL SPECS:

### Gas Models

SERVICE VOLTAGE	PHASE	WIRE SERVICE	APPROX AMP DRAW		CIRCUIT BREAKER
			60 Hz	50 Hz	
<b>GAS</b>					
120	1ø	2	10.3	--	15
200	1ø	2	8.7	8.8	15
208	1ø	2	8.4	--	15
220	1ø	2	8.1	8.1	15
230	1ø	2	--	7.4	15
240	1ø	2	7.7	7.0	15

\* Energy efficiency depends on load and installation.



**Innovating Revolutions in Laundry**

(508) 678-9000 • (508) 678-9447 fax • sales@amdry.com • www.amdry.com

# ES-35/35

MAXIMUM CAPACITY (DRY WEIGHT) PER POCKET		35 lb	15.88 kg
TUMBLER DIAMETER		30"	76.20 cm
TUMBLER DEPTH		30"	76.20 cm
TUMBLER VOLUME PER POCKET		12.33 cu ft	349.15 L
TUMBLER/DRIVE MOTOR PER POCKET		1/4 hp	0.19 kW
BLOWER/FAN MOTOR PER POCKET		1/2 hp	0.37 kW
DOOR OPENING (DIAMETER)		19-3/8"	49.21 cm
DOOR SILL HEIGHT TOP POCKET / BOTTOM POCKET		54-11/16" / 14-7/8"	138.91 cm / 37.78 cm
WATER CONNECTION		N / A	
DRYERS PER 20'/40' CONTAINER		14 / 28	
DRYERS PER 53' TRUCK		36	
<b>Gas</b>	VOLTAGE AVAILABLE	120v 1ø 2w	60 Hz
	APPROXIMATE NET WEIGHT	600 lb	272.16 kg
	APPROXIMATE SHIPPING WEIGHT	630 lb	285.76 kg
	AIRFLOW PER POCKET	380 cfm	10.76 cmm
	HEAT INPUT PER POCKET	64,000 Btu/hr	16,138 kcal/hr
	EXHAUST CONNECTION (DIAMETER) PER POCKET	6"	15.24 cm
	COMPRESSED AIR CONNECTION	N / A	
	COMPRESSED AIR VOLUME	N / A	
	INLET PIPE CONNECTION PER POCKET	1/2" M.N.P.T.	
	<b>Electric</b>	VOLTAGE AVAILABLE	N / A
APPROXIMATE NET WEIGHT		N / A	
APPROXIMATE SHIPPING WEIGHT		N / A	
AIRFLOW PER POCKET		N / A	
EXHAUST CONNECTION (DIAMETER) PER POCKET		N / A	
COMPRESSED AIR CONNECTION		N / A	
COMPRESSED AIR VOLUME		N / A	
<b>Steam</b>	OVEN SIZE PER POCKET		
	kW	Btu/hr	kcal/hr
	VOLTAGE AVAILABLE	N / A	
	APPROXIMATE NET WEIGHT	N / A	
	APPROXIMATE SHIPPING WEIGHT	N / A	
	AIRFLOW PER POCKET	N / A	
	STEAM CONSUMPTION PER POCKET	N / A	
	OPERATING STEAM PRESSURE	N / A	
	EXHAUST CONNECTION (DIAMETER) PER POCKET	N / A	
	COMPRESSED AIR CONNECTION	N / A	
	COMPRESSED AIR VOLUME	N / A	
BOILER HORSEPOWER (NORMAL LOAD) PER POCKET	N / A		
SUPPLY CONNECTION PER POCKET	N / A		
RETURN CONNECTION PER POCKET	N / A		

Shaded areas are stated in metric equivalents

Justin Sampson 9/9/09

